



GLACIÄR MIDI

SIMPLY RELIABLE REFRIGERANT GAS DETECTORS

www.samon.se



GLACIÄR MIDI

GLACIÄR MIDI detects leaks of refrigerant gases that are harmful to the environment we live in, and harmful to the environments that people work in. By mitigating these leaks, our planet is protected against greenhouse gas emissions, our colleagues stay safe and healthy, and property is protected against the risks of system failure and explosion.

SIMPLE SELECTION

GLACIÄR MIDI can be configured for detection of synthetic refrigerants (HFC & HFO blends), natural refrigerants including CO₂, NH₃ and R290 (propane), and other hydrocarbon gases. We have used our extensive gas detection expertise to make it possible to detect all commonly used refrigerants with only 5 different sensor types, making it simple and easy to select the right detector for your application.



SYSTEMS INTEGRATION

A range of connectivity choices are available for integration of **GLACIÄR MIDI** into refrigeration control systems and/or building management systems. Modbus, analogue output, and relay contacts are available as standard. Installation is made easy by the availability of multiple cable glands located for easy access.



SENSOR SELECTION

- All sensor types compatible with the **GLACIÄR MIDI** detector platform
- HFC/HFO blends detected via just two broad-band sensor variants
- CO₂ detection via infra-red sensor
- Electrochemical sensors for NH₃ detection
- R290 (propane) & hydrocarbon sensor


EASY INSTALLATION

- Comes ready to install with standard configuration
- Multiple cable glands located for easy access to power connections & output terminals
- Pluggable screw terminals for simple installation on site
- IP67-rated enclosure & -40°C - + 50°C operating range suitable for all refrigeration environments

THE SIMPLY RELIABLE REFRIGERANT GAS DETECTOR

Protect the environment, protect people, protect property

More information
about **GLACIÄR MIDI**



DESIGNED WITH YOU IN MIND

SAMON has drawn on over 30 years' experience in the refrigeration industry to design a gas detector to meet the needs of every user. Providing interfaces for set-up, configuration, and maintenance via both a digital app connection and via an analogue service-wheel, **GLACIÄR MIDI** can be used in all refrigeration environments without the need for any special tools.



RELIABLE PERFORMANCE

SAMON products have a warranty rate of less than 0.001% - we understand how important reliability is to our customers and build it into everything we do. **GLACIÄR MIDI** is designed to be robust and reliable in machinery rooms, cold rooms, and the harshest of industrial refrigeration applications.

MULTIPLE CONFIGURABLE OUTPUTS

- Alarm indication via relay contacts for high- and low-alarm levels
- Interface to control systems via Modbus RTU over RS485 & selectable analogue output range
- Visual health-check via high-intensity status LEDs
- Selectable dedicated fault relay

INTELLIGENT SERVICE & MAINTENANCE

- Service counter tells you when service is needed
- Bluetooth® connectivity to app for configuration & calibration (Android™ & iOS)
- Analogue configuration via service-wheel & magnetic switch
- Pre-calibrated sensor module replacements
- Sensor lifetime counter

TECHNICAL DATA

Analogue Output	
Selectable analogue output range	1...5V; 0...10V; 2...10V; 4...20mA (default)
Modbus RTU over RS-485	
Connection	Galvanically isolated (optocoupler)
Baud rate	9,600 or 19,200 (default)
Data bits	8
Parity	None (default), odd, even
Stop bits	1 or 2 (default)
Other Interfaces	
Visible indicator	Multi-color Status LED
Bluetooth®	BLE (Service app)
Relays	2 SPDT 1 A at 24 VAC/VDC, resistive load
Switches	Service wheel (x1) and Magnetic (x1)
Analogue service output	0-10VDC
Power Supply	
Operating voltage	15 to 24 VDC; 24 V AC/DC, 50/60 Hz (Selected automatically)
Operating effect and current, max.	4W, 170mA @ 24VDC
Wiring	
Power supply	28 to 16 AWG / 0.75 mm ² to 1.5 mm ²
Analogue signals and relays	28 to 16 AWG / 0.75 mm ² to 1,5 mm ²
Modbus network	3-core, 2 twisted pair + ground, shielded cable with 120 Ω characteristic impedance, 24 to 16 AWG / 0.25 mm ² to 1.5 mm ² , maximum length 300 meters.
Cable gland	4 x M16, 4-8mm cable outer diameter
Cable rating	UL 2556 VW-1 or equivalent
Dimensions	
Enclosure Size (W×H×D)	Built-In: 134x102x54 mm Remote, main enclosure: 134x102x54 mm Remote, sensor enclosure: 103x50 mm
Weight	Built-In: 430 g Remote: 660 g
Environmental	
Operating temperature	-40° to 50° Celsius
Storage temperature	-40° to 50° Celsius
Humidity	5 to 90 %RH, non-condensing
Enclosure protection	IP67
Enclosure material	Polycarbonate

Applicable standards

Directives	Standards
(EMC) 2014/30/EU	EN 61010-1 IEC 60529
(LVD) 2014/35/EU	EN 378 IEC 60355-2-40,
(RED) 2014/53/EU	EN 14624 Annex LL (Pending)
	EN 50270
	EN 50271

