

# HFDC-24FIBER



HELIAX® Fiber Distribution Closure 24 fibers - 12 DLCs UPC.

## Product Classification

<b>Regional Availability</b>	China   EMEA   Europe   India   Latin America   Middle East/Africa   North America
<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Outdoor junction box
<b>Product Brand</b>	HELIAX®

## General Specifications

<b>Application</b>	Used as a fiber junction box
<b>Total Fiber Adapters</b>	12
<b>Color</b>	Black
<b>Doors, quantity</b>	2
<b>Mounting</b>	Pipe, 44–114 mm (1.75–4.5 in) OD   Wall
<b>Total Fibers, quantity</b>	24
<b>Total Ports, quantity</b>	12

## Dimensions

<b>Height</b>	370.84 mm   14.6 in
<b>Width</b>	215.9 mm   8.5 in
<b>Depth</b>	113.03 mm   4.45 in
<b>Jumper Breakout Length, Maximum</b>	85 mm   3.346 in
<b>Jumper Outlet, Quantity, Maximum</b>	12
<b>Jumper Outlet Diameter, Minimum</b>	0 mm   0 in
<b>Jumper Outlet Diameter, Maximum</b>	7 mm   0.276 in
<b>Trunk Entry, Diameter, Maximum</b>	4 mm   0.157 in

## Material Specifications

<b>Material Type</b>	High-impact polycarbonate, UV resistant
----------------------	---

# HFDC-24FIBER

---

## Mechanical Specifications

**Impact Test Method** EN62262 | IEC62262: IK07

## Environmental Specifications

**Operating Temperature** -40 °C to +75 °C (-40 °F to +167 °F)

**Qualification Standards** IEC 60529, IP68

## Packaging and Weights

**Included** Mounting kit

**Weight, net** 2.649 kg | 5.84 lb